

EU-TYPE EXAMINATION (MODULE B) CERTIFICATE

Radio Equipment Directive (RED) 2014/53/EU

PHOENIX TESTLAB

Notified Body Number 0700



BNetzA-bS-02/51-55

This is to certify that:

Product Description

PHOENIX TESTLAB did undertake the relevant type examination procedures for the radio equipment identified below which was found to be in compliance with the essential requirements of Radio Equipment Directive (RED) 2014/53/EU subject to any conditions in the annex attached hereto.

Certificate No. 17-213645

ShenZhen Chainway Information Technology Manufacturer

Co.,Ltd

9/F, Building 2, Phase 2, Daqian Industrial Park, Address

Longchang Rd., District 67, Bao'an, Shenzhen,

China

Mobile Data Terminal; with GPS, GSM, Bluetooth,

WIFI, WCDMA, NFC, Non-specific SRD and

Inductive applications

Brand Name / Model Name CHAINWAY / C4000

The radio equipment meets the following essential requirements

Article 3.1 a): Health and Safety Conform

Conform Article 3.1 b): Electromagnetic Compatibility

Article 3.2: Effective and Efficient Use of Radio Spectrum Conform

Additional Essential Requirements: Not applicable

Date of issue 2017-11-08 Expiry date: 2022-11-07

This certificate remains valid unless cancelled or revoked, provided the conditions in the attached annex are complied with. The conditions for the validity of this certificate are listed in the Annex.

The attached Annex forms part of this certificate. This certificate consists of 4 pages.

Signed by Alan Lane **Notified Body**

> PHOENIX TESTLAB GmbH Königswinkel 10 D-32825 Blomberg, Germany www.phoenix-testlab.de

Date 08 November 2017

Annex

Technical description

GSM 850/900/1800/1900 MHz Frequency Range

> Bluetooth: 2402 - 2480 MHz WiFi(H20): 2412 - 2472 MHz WiFi(H40): 2422 - 2462 MHz

UTRA FDD Band I

Inductive applications: 125KHz

Non-specific SRD: 865.7-867.5 MHz (4CH, duty cycle <0.1%)

NFC:13.56 MHz

GPS: 1575.42 MHz (RX)

Transmitted Power Max.2W / Max.1W

> Bluetooth: 0.10 dBm EIRP WiFi: 12.90 dBm EIRP UTRA FDD: 24 dBm

Inductive applications: -19.1 dBµA/m at 10m

Non-specific SRD: 11.0 dBm ERP NFC: -0.332 dBµA/m at 10m

Duty Cycle Non-specific SRD :868.28 MHz : < 1%

Hardware Version C4000-MB-V6.0

Software Version V1.0.0-10040006582-2017-6-16

System Components

935161, 3.7V / 3200mAh Battery

(Spring Power Technology(Shenzhen)Company Limited.)

Optional Components

G101T-050200-1 Adapter

Input:100-240V, 50/60Hz, 0.28A; Output: 5V/2A

(GME Technology(Shenzhen)Co.,Ltd)

USB Cable MIXL-C3000-USB-V20, 1.0 meter



Approval documentation

External / Internal Photos Provided, 7 pages / 14 pages

User Manual C4000 Handheld Terminal User Manual, 27 pages

Block Diagram Provided, 1 page

Circuit Diagram Provided, 17 pages/1 page/1 pa Operational Description OPERATIONAL DESCRIPTION OF C4000, 5 pages

PCB Layout Provided, 4 pages/ 11 pages/ 12 pages/10 pages/ 10 pages

Parts Placement Provided, 2 pages/ 2 pages/2 pages/2 pages

Parts List Provided, 5 pages/1 page/1 page/1 page/1 page

3 pages, October 24, 2017 **EU Declaration of Conformity** Explanation of compliance Article 10(2) and Article 10(10)

Description in the User Manual

Further Documents Risk Assessment, 3 pages, October 24, 2017

Applied Standards and Test Reports

Specification	Laboratory	Test Report Number Version
EN 60950-1:2006+A11:2009+ A1:2010+A12:2011+A2:2013	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10396
EN 50360:2001+A1:2012 EN 50566:2013/AC:2014 EN 62209-1:2006 EN 62209-2:2010 EN 62479:2010	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10590
Draft ETSI EN 301 489-1 V2.2.0 Final Draft ETSI EN 301 489-3 V2.1.1 Draft ETSI EN 301 489-17 V3.2.0 Draft ETSI EN 301 489-19 V2.1.0 Draft ETSI EN 301 489-52 V1.1.0	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10601
ETSI EN 300 328 V2.1.1	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10317
ETSI EN 301 511 V9.0.2	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10577
ETSI EN 301 908-1 V11.1.1 ETSI EN 301 908-2 V11.1.1	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10578
ETSI EN 300 220-1 V3.1.1 ETSI EN 300 220-2 V3.1.1	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10321
ETSI EN 300 330 V2.1.1	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10319 SET2017-10320
ETSI EN 303 413 V1.1.1	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.	SET2017-10318



Limitations / Restrictions

- This device also contains frequency bands that are not operational in EU member states. Only the frequency bands used in European Union have been assessed for this Certificate.
- Operating Temperature range is -10 +40 degree Celsius.
- Body SAR Separation distance is 5mm.

Notes

- 1. This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with PHOENIX TESTLAB.
- 2. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/them being placed on the market.
- 3. The manufacturer shall take all measures necessary so that the manufacturing process and its monitoring ensure conformity of the manufactured radio equipment with the approved type described in the EU-type examination certificate and with the requirements of Directive 2014/53/EU that apply to it.
- 4. The manufacturer shall affix the CE marking to each item of radio equipment that is in conformity with the type described in the EU-type examination certificate and satisfies the applicable requirements of the Directive.
- 5. The manufacturer shall draw up a written EU declaration of conformity for each radio equipment type and keep it at the disposal of the national authorities for 10 years after the radio equipment has been placed on the market. The EU declaration of conformity shall identify the radio equipment type for which it has been drawn up. A copy of the EU declaration of conformity shall be made available to the relevant authorities upon request.

