CHAINWAY®



C90

Mobile Computer









WiFi



Bluetooth



1D Barcode



2D Barcode



NFC



GMS



Camera



GNSS



Al Engine

Chainway C90 is our newly-developed, lightweight and portable handheld terminal that exhibits extremely powerful performance. Built with Android 10 OS and high-performance octa-core processor, it features vigorous system configuration. With rich functionality features like outstanding barcode scanning, sturdy WiFi performance, NFC, front and rear cameras, it possesses the best price versus performance ratio. All these make C90 immensely perfect to be implemented in a wide spectrum of industries, including logistics, warehousing, retail, asset tracking etc., assisting customers to improve operation and management levels significantly.











Specification

Physical Cha	aracteristics
Dimensions	158.5 x 76.0 x 13.1 mm / 6.24 x 2.99 x 0.52 in.
Weight	230g / 8.11 oz. (device with battery)
Keypad	Power, 2 scan keys, volume +/-
Battery	Main battery: built-in 5000 mAh
	Standby: up to 490 hours (only main battery; WiFi: up to 470h; 4G: up to 440h)
	Continuous use: over 12 hours (depending on user environment)
	Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Sensor	Light sensor, proximity sensor, gravity sensor
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; receiver
Display	5.7-inch (18:9) , IPS LTPS 1440 x 720
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Card slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB Type-C, USB 2.0, OTG
Performance	e
CPU	Cortex-A53 2.0 GHz Octa-core
RAM+ROM	3GB+32GB / 3GB+64GB / 4GB+64GB
Expansion	Supports up to 128 GB Micro SD card
Developing	Environment
Operating System	Android 10, GMS, FOTA, Soti MobiControl, Android Enterprise Recommended, Zero-Touch, 90-day security updates, SafeUEM supported; Built-in support for a future upgrade through Android 11/12 which complies with GMS and Android Enterprise Recommended
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio
User Environ	nment
Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.92 ft. drops to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
	IDC7 IEC liss ifi tiss
Sealing	IP67 per IEC sealing specifications

WLAN	Support IEEE802.11 a/b/g/n/ac/d/e/h/i/k/r/v/w, 2.4G/5G dualband, IPV4, IPV6; Support 5G PA
	Fast roaming: PMKID caching, 802.11r, OKC
	Operating Channels: 2.4G(channel 1°13), 5G(channel 36,38,40,42,44,46,48,52,56,60,64,100,104,108,1 12,116,120,124,128,132,136,140,149,153,157,161,165), depends on local regulations
	Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS, PEAP-GTC, etc.
WWAN(Europe/ Asia)	2G: GSM850/GSM900/DCS1800/PCS1900
	3G: CDMA EVDO: BC0
	WCDMA: B1/B2/B4/B5/B8
	TD-SCDMA: A/F(B34/B39)
	4G: B1/B2/B3/B4/B5/B7/B8/B20/B34/B38/B39/B40/B41
WWAN(America)	2G: GSM850/GSM900/DCS1800/PCS1900
	3G: CDMA EVDO: BC0/BC1
	WCDMA: B2/B4/B5/B8
	4G: B2/B4/B5/B7/B8/B12/B17/B28A/B28B/B38
Bluetooth	V2.1+EDR, 3.0+HS and V4.1+HS, BT5.0
GNSS	000/4000 0104/400 0 10 0 11 1 1 1 1
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna
Data Collec	
Data Collec	
Data Collec	tion
Data Collect Camera Front Camera	tion 5MP
Data Collect Camera Front Camera Rear Camera	tion 5MP
Data Collect Camera Front Camera Rear Camera NFC	5MP Rear 16MP Autofocus with flash
Data Collect Camera Front Camera Rear Camera NFC Frequency	5MP Rear 16MP Autofocus with flash 13.56 MHz
Data Collect Camera Front Camera Rear Camera NFC Frequency Protocol	5MP Rear 16MP Autofocus with flash 13.56 MHz ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Camera Front Camera Rear Camera NFC Frequency Protocol Chips	tion 5MP Rear 16MP Autofocus with flash 13.56 MHz ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. M1 card (S50, S70), CPU card, NFC tags, etc. 2-4 cm
Data Collect Camera Front Camera Rear Camera NFC Frequency Protocol Chips Range	tion 5MP Rear 16MP Autofocus with flash 13.56 MHz ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. M1 card (S50, S70), CPU card, NFC tags, etc. 2-4 cm
Camera Front Camera Rear Camera NFC Frequency Protocol Chips Range Barcode Scann	tion 5MP Rear 16MP Autofocus with flash 13.56 MHz ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. M1 card (550, S70), CPU card, NFC tags, etc. 2-4 cm ning (optional) Honeywell: N6603 / N6703; CM60 UPC/EAN, Code128, Code39, Code93, Code11, Interleaved
Camera Front Camera Rear Camera NFC Frequency Protocol Chips Range Barcode Scanner	5MP Rear 16MP Autofocus with flash 13.56 MHz ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. M1 card (S50, S70), CPU card, NFC tags, etc. 2-4 cm ning (optional)

 $Notice: Product \ specifications \ are \ subject \ to \ change \ without \ prior \ notice. \ / \ Model: \ C90 \ / \ Update \ Date: \ 2024-04-01$